IN THE CLAIMS:

Please cancel claims 1, 13, 17, and 25 and amend the claims as follows:

1. (Cancelled)

2. (Currently Amended) An apparatus for handling a tubular, the apparatus being coupled to a tubular transport tool for transporting the tubular to a wellbore, comprising:

at least one arm ~~having a first end and a second end~~, the ~~first end~~ arm ~~being~~ operatively coupled to a body, the body coupled to the tubular transport tool, wherein the at least one arm is movable in two or more planes relative to the body, and

wherein the at least one arm ~~second end~~ is actuatable to limit movement of the tubular relative to the tubular transport tool.

3. (Currently Amended) The apparatus of claim 2, wherein ~~the at least one arm is operatively coupled to a body, and~~ the body is movably coupled to the tubular transport tool.

4. (Original) The apparatus of claim 3, wherein the tubular is retained between the body and the at least one arm.

5. (Currently Amended) The apparatus of claim 2, wherein the arm ~~second end~~ includes a stop member for contacting the tubular.

6. (Original) The apparatus of claim 5, wherein the apparatus comprises two arms and the stop member is adapted to retain the tubular between the two arms.

7. (Original) The apparatus of claim 2, wherein two arms are provided to control the movement of the tubular.

8. (Original) The apparatus of claim 7, wherein the two arms are actuatable between an open position and a closed position.

9. (Original) The apparatus of claim 8, wherein the stop members are adapted to retain the tubular between the two arms when the two arms are in the closed position.

10. (Original) The apparatus of claim 9, wherein each arm includes a stop member.

11. (Original) The apparatus of claim 7, wherein the two arms are actuatable between a raised position and a lowered position.

12. (Currently Amended) The apparatus of claim 11, wherein the two arms are adapted to control the movement of tubular when the arms are in the raised position.

13. (Cancelled)

14. (Currently Amended) A method of positioning a tubular above a wellbore, the tubular having a first end and a second end, the method comprising:

providing a tubular transport tool having a tubular handling apparatus having two or more arms;

transporting the tubular to a position proximate the wellbore;

raising the first end of the tubular relative to the wellbore; ~~and~~

engaging the second end of the tubular with the two or more arms;

removing the second end of the tubular from the transport tool; and

~~limiting movement of the second end using the tubular handling apparatus; and~~

positioning the second end above the wellbore ~~using the tubular transport tool~~.

15. (Original) The method of claim 14, wherein the tubular handling apparatus is operatively coupled to the tubular transport tool.

16. (Original) The method of claim 14, further comprising actuating the tubular handling apparatus to contact the second end of the tubular as the tubular is raised.

17. (Cancelled)

18. (Currently Amended) The method of claim [[17]] 14, further comprising raising the two or more arms [[arm]] to contact the tubular, thereby limiting movement of the second end.

19. (Currently Amended) The method of claim 14, wherein the tubular is disposed between two or more arms of the tubular handling apparatus.

20. (Original) The method of claim 14, further comprising retaining the first end of the tubular with an elevator.

21. (Original) The method of claim 14, wherein the second end is positioned above the wellbore using the tubular handling apparatus.

22. (Currently Amended) An apparatus for transporting a tubular to a wellbore, comprising:

a carriage for receiving the tubular; and

a tubular handling tool for limiting movement of the tubular as the tubular is removed from the carriage, wherein the tubular handling tool is operatively coupled to the carriage and has two or more arms adapted to pivotably move the tubular from the carriage to the wellbore.

23. (Currently Amended) The apparatus of claim 22, wherein the ~~tubular handling tool comprises at least one arm having~~ two or more arms have a first end and a second end, the first end being operatively coupled to the ~~trough~~ carriage and the second end actuatable to contact the tubular.

24-26. (Cancelled)

27. (Original) The apparatus of claim 26, wherein the two arms are movable between an open position and a closed position for retaining the tubular.

28. (Original) The apparatus of claim 22, further comprising a ramp for guiding movement of the carriage.

29. (Currently Amended) The apparatus of claim 22, further comprising a transport mechanism ~~moving means~~ for moving the carriage.

30. (Original) The apparatus of claim 29, further comprising a ramp for guiding movement of the carriage.

31. (Original) The apparatus of claim 22, wherein the carriage comprises a trough.

Please add the following new claim:

32. (New) A method of positioning a tubular above a wellbore, the tubular having a first end and a second end, the method comprising:

providing a carriage having a tubular handling apparatus having one or more arms;

transporting the carriage with the tubular to a position proximate the wellbore;

lifting the first end of the tubular substantially over the wellbore;

engaging the second end of the tubular with the one or more arms;

pivoting the one or more arms in a first plane while removing the second end of the tubular from the carriage; and

pivoting the one or more arms in a second plane to release the tubular when the second end is substantially over the wellbore.